

Waterproof Pocket Tester



- 只需1-2顆AAA電池即可運行，節能環保
- 超大範圍量程，高精密解析度
- 自動關機，數據儲存功能和低電量提示
- 大螢幕LCD，儲能背光，方便暗處讀值
- 維護簡單，無需任何工具可輕易更換電池和電極
- 記憶功能：10 組
- 尺寸/重量：164x37x40 mm / 90 g



酸鹼度 PH30

- 測量：-2.00~16.00pH
- 溫度：0.0~60.0°C/32.0~140.0°F
- 解析度：0.01pH, 0.1°C/°F
- 準確度：±0.01pH



氧化還原ORP30

- 測量：-900~+900mV
- 溫度：0.0~60.0°C/32.0~140.0°F
- 解析度：1mV, 0.1°C/1°F
- 準確度：±1mV



電導度 CON30

- 0~200.0 uS/cm, 0~2000 uS/cm
0~20.00 mS/cm, 0~50.0 mS/cm
TDS：0~50 ppt SAL：0~30 ppt
- 溫度：0.0~60.0°C/32.0~140.0°F
- 解析度：0.1, 1uS/cm(ppm), 0.01, 0.1mS/cm(ppt)

可換式電極

■ 維護簡單，可更換式的精密量測電極，全系列無需任何工具可輕易更換電極。



PH



DO



FCL



ORP



CON



DOZ



定速流通槽

定速
使用



- 可搭配DO/FCL/DOZ測量使用
- 定速旋轉水流，穩定測試數值
- 兩顆AA電池，更換電池輕鬆簡單



溶氧 DO30

- 測量範圍：0.00~20.00mg/L
0.0~200.0%
- 溫度範圍：0.0~60.0°C/ 32.0~140.0°F
- 解析度：0.01mg/L 0.1% 0.1°C/0.1°F
- 準確度：±1.5%F.S. ±0.3°C/0.5°F



餘氯 FCL30

- 測量範圍：0.05~10.00ppm
- 溫度範圍：0.0~60.0°C
32.0~140.0°F
- 解析度：0.01ppm/0.1°C/1°F
- 準確度：±2%F.S.



臭氧 DOZ30

- 測量範圍：0.05~5.00ppm
- 溫度範圍：0.0~60.0°C
32.0~140.0°F
- 解析度：0.01ppm
- 準確度：±2%F.S.